

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20605M3W3 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-957-2376 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20605M3W3 Specifications

| | |
|--|--|
| Fastener Length: | 0.265 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Pull Through Hollow Shank |
| Head Major Diameter: | 0.179 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| End Item Identification: | 9w/s:aircraft, T-38; Aircraft, Eagle F-15; Deep Submergence Systems Programs (dssp); Aircraft, Phantom F-4; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); F-22 Raptor Air Dominance Fighter; Aircraft, Galaxy C-5; Aircraft, F-111; Aircraft, Tomcat F-14 |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Shear Strength: | 70 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605M3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.