

**Description**

Fastener Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605M3W4
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-173-8782
Schedule B:	8308.90.9000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20605M3W4 Specifications

<b>Fastener Length:</b>	0.320 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Sleeve Or Nickel Alloy R-405 Sleeve
<b>Material:</b>	Nickel Alloy 400 Stem Or Nickel Alloy R-405 Stem
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Sleeve
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec All Material Responses Stem
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Surface Treatment:</b>	Cadmium Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605M3W4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.