

**Description**

Fastener Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20605ML3W2
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-029-8206
Schedule B:	8308.90.9000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20605ML3W2 Specifications

<b>Fastener Length:</b>	0.203 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.032 Inches Minimum And 0.040 Inches Maximum
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.179 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film Or Wax
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Shear Strength:</b>	105 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605ML3W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.