

Description

Fastener Length: 1/4", MS20605 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | MS20605ML3W3 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5320-01-289-6937 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS20605ML3W3 Specifications

| | |
|---|--|
| Fastener Length: | 0.265 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.179 Inches Minimum And 0.183 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Nickel Alloy 400 Sleeve |
| Material: | Nickel Alloy 400 Stem |
| Material Document And Classification: | Qq-n-281 CI A Fed Spec Single Material Response Sleeve |
| Material Document And Classification: | Qq-n-281 CI A Fed Spec Single Material Response Stem |
| Surface Treatment: | Silver Sleeve |
| Surface Treatment: | Silver Stem |
| Surface Treatment Document And Classification: | Qq-s-365 Fed Spec Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-s-365 Fed Spec Single Treatment Response Stem |
| Specification/standard Data: | 96906-ms20605 Government Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605ML3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.