

Description

Fastener Length: 1/4", MS20605 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605ML3W3
Minimum Qty (MOQ):	25
NSN:	5320-01-289-6937
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS20605ML3W3 Specifications

Fastener Length:	0.265 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.179 Inches Minimum And 0.183 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Nickel Alloy 400 Sleeve
Material:	Nickel Alloy 400 Stem
Material Document And Classification:	Qq-n-281 CI A Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-n-281 CI A Fed Spec Single Material Response Stem
Surface Treatment:	Silver Sleeve
Surface Treatment:	Silver Stem
Surface Treatment Document And Classification:	Qq-s-365 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-s-365 Fed Spec Single Treatment Response Stem
Specification/standard Data:	96906-ms20605 Government Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605ML3W3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.