

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605MP3W2
Minimum Qty (MOQ):	20 EA
NSN:	5320-00-143-6273
Schedule B:	8308.90.9000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20605MP3W2 Specifications

Fastener Length:	0.203 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.179 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Shear Strength:	105 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605MP3W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.