

**Description**

Fastener Length: 7/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605R3W12
Minimum Qty (MOQ):	25
NSN:	5320-01-490-3196
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20605R3W12 Specifications

<b>Fastener Length:</b>	0.905 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.688 Inches Minimum And 0.750 Inches Maximum
<b>Countersink Angle:</b>	98.0 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Asstm A495 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-a-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605R3W12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.