

# P/N MS20605R3W9

## **Description**

MS20605R3W9 Blind Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

### CCR264CS3-09

SKU / Model: MS20605R3W9

Minimum Qty (MOQ): 10

NSN: 5320-01-335-9285

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20605R3W9 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.179 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.501 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	89.0 Degrees Minimum And 111.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall

# **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS20605R3W9">https://military-fasteners.com/rivets/blind+rivets/MS20605R3W9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.