

**Description**

Cherry Pull-thru Rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20605R4W2
Minimum Qty (MOQ):	50 EA
NSN:	5320-01-343-1013
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20605R4W2 Specifications

<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.123 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Pull Through Hollow Shank
<b>Head Major Diameter:</b>	0.229 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Astm A495 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605R4W2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.