

Description

Fastener Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | MS20605R4W8 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-490-6205 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N MS20605R4W8 Specifications

| | |
|---|--|
| Fastener Length: | 0.693 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.123 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.221 Inches Minimum And 0.229 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Lubrication: | Dry Film |
| End Item Identification: | F-22 |
| Grip Length: | 0.438 Inches Minimum And 0.500 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Rivet |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Steel Comp 305 Stem |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Astm A-493 Assn Std Single Material Response Stem |
| Surface Treatment: | Passivate Sleeve |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Ams Qq-p-35 Assn Std Single Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Ams Qq-p-35 Assn Std Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605R4W8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.