

Description

Cherry Pull-thru Rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20605R4W9
Minimum Qty (MOQ):	40 EA
NSN:	5320-01-519-6792
Schedule B:	7318.23.0000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS20605R4W9 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film
End Item Identification:	F-22
Grip Length:	0.563 Inches Nominal
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm A-493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Sleeve
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this cherry pull-thru rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605R4W9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.