

Description

Fastener Length: 1/4", MS20605 series rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20605S3C3
Minimum Qty (MOQ):	50
NSN:	5320-01-420-0969
Schedule B:	7318.23.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS20605S3C3 Specifications

Fastener Length:	0.265 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.179 Inches Minimum And 0.183 Inches Maximum
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Minimum Tensile Strength:	155 Pounds Per Square Inch
Shear Strength:	105 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 1008 Overall Or Steel Comp 1012 Overall Or Steel Comp 1018 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Test Data Document:	81349-mil-r8814 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Specification/standard Data:	96906-ms20605 Government Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605S3C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.