

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20605S3C5
Minimum Qty (MOQ):	60 EA
NSN:	5320-01-420-0972
Schedule B:	7318.23.0000
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N MS20605S3C5 Specifications

<b>Fastener Length:</b>	0.390 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.179 Inches Minimum And 0.183 Inches Maximum
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Minimum Tensile Strength:</b>	155 Pounds Per Square Inch
<b>Shear Strength:</b>	105 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 1008 Overall Or Steel Comp 1012 Overall Or Steel Comp 1018 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
<b>Test Data Document:</b>	81349-mil-r8814 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
<b>Specification/standard Data:</b>	96906-ms20605 Government Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605S3C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.