

Description

Fastener Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20605S3W12
Minimum Qty (MOQ):	65 EA
NSN:	5320-01-345-1020
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20605S3W12 Specifications

Fastener Length:	0.828 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.183 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 1008 Sleeve Or Steel Comp 1012 Sleeve Or Steel Comp 1018 SleeveSteel Comp 1008 Stem
Material Document And Classification:	Astm A545 Assn Std All Material Responses Sleeveastm A545 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate SleeveCadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeveqq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS20605S3W12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.