

**Description**

Fastener Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206132C4
Minimum Qty (MOQ):	50
NSN:	5320-00-721-7357
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20613-2C4 Specifications

<b>Fastener Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Shank Diameter:</b>	0.061 Inches Minimum And 0.065 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.119 Inches Minimum And 0.131 Inches Maximum
<b>Grip Length:</b>	0.146 Inches Minimum And 0.166 Inches Maximum
<b>Shear Strength:</b>	65000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Comp 302 Overall
<b>Material Document And Classification:</b>	Qq-w-423,cond A Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-2C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.