

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS206132C5 |
| Minimum Qty (MOQ): | 75 EA |
| NSN: | 5320-00-777-5799 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20613-2C5 Specifications

| | |
|---|--|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.027 Inches Minimum And 0.037 Inches Maximum |
| Shank Diameter: | 0.061 Inches Minimum And 0.065 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.119 Inches Minimum And 0.131 Inches Maximum |
| Shear Strength: | 65000 Single Pounds Per Square Inch |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | 66,300 Series Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Nondefinitive Spec/std Data: | 14 Type And C Grade |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-2C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.