

**Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206132P4
Minimum Qty (MOQ):	75 EA
NSN:	5320-00-687-8135
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20613-2P4 Specifications

<b>Fastener Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Shank Diameter:</b>	0.061 Inches Minimum And 0.065 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.119 Inches Minimum And 0.131 Inches Maximum
<b>Shear Strength:</b>	25000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Comp 1005 Overall Or Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	14 Type And E Grade

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-2P4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.