

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206132P8
Minimum Qty (MOQ):	100
NSN:	5320-00-068-6925
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20613-2P8 Specifications

<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Shank Diameter:</b>	0.061 Inches Minimum And 0.065 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.119 Inches Minimum And 0.131 Inches Maximum
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Comp 1005 Overall Or Steel Comp 1015 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-2P8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.