

P/N MS20613-2P8

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS206132P8

Minimum Qty (MOQ): 100

NSN: 5320-00-068-6925

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









P/N MS20613-2P8 Specifications

Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Universal
Head Height:	0.027 Inches Minimum And 0.037 Inches Maximum
Shank Diameter:	0.061 Inches Minimum And 0.065 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.119 Inches Minimum And 0.131 Inches Maximum
Heat Treatment:	Annealed Overall
Material:	Steel Comp 1005 Overall Or Steel Comp 1015 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20613-2P8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.