

Description

Fastener Length: 3/4", MS20613 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS206133C12 |
| Minimum Qty (MOQ): | 1000 |
| NSN: | 5320-00-766-2307 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N MS20613-3C12 Specifications

| | |
|--|---|
| Fastener Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Grip Length: | 0.599 Inches Minimum And 0.619 Inches Maximum |
| Shear Strength: | 65000 Single Pounds Per Square Inch |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Comp 302 Overall |
| Material Document And Classification: | Qq-w-423,cond A Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-3C12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.