

Description

length: 1/4", diameter: 3/32", universal head, corrosion resistant steel, roughly 1300 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206133C4
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-721-8972
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20613-3C4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Grip Length:	0.099 Inches Minimum And 0.119 Inches Maximum
Shear Strength:	65000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Steel Comp 302 Overall
Material Document And Classification:	Qq-w-423,cond A Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-3C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.