

## P/N MS20613-3P4

### **Description**

Fastener Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS206133P4

Minimum Qty (MOQ): 505 EA

NSN: 5320-00-068-6926

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20613-3P4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.047 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.094 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Surface Treatment:	Cadmium Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4">https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4">https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4">https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4">https://military-fasteners.com/rivets/solid+rivets/MS20613-3P4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/ms20613-3P4">https://military-fasteners.com/rivets/solid+rivets/ms20613-3P4</a> and selecting the quantity you want then cart in the properties of the properti