

Description

Fastener Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206133P7
Minimum Qty (MOQ):	130 EA
NSN:	5320-00-061-8219
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20613-3P7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Shear Strength:	25000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Steel Comp 1005 Overall Or Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	14 Type And E Grade

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-3P7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.