

Description

Fastener Length: 5/8", roughly 340 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS206134C10 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-062-6628 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N MS20613-4C10 Specifications

| | |
|--|---|
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Grip Length: | 0.427 Inches Minimum And 0.447 Inches Maximum |
| Shear Strength: | 65000 Single Pounds Per Square Inch |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Comp 302 Overall |
| Material Document And Classification: | Qq-w-423,cond A Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-4C10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.