

## P/N MS20613-4C15

### **Description**

Fastener Length: 15/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS206134C15

Minimum Qty (MOQ): 45 EA

NSN: 5320-01-501-8759

Schedule B: 7318.23.0000

ECCN: 9A991

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20613-4C15 Specifications

Fastener Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Head Style:	Universal
Head Height:	0.027 Inches Minimum And 0.037 Inches Maximum
Shank Diameter:	0.061 Inches Minimum And 0.065 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.119 Inches Minimum And 0.131 Inches Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Astm A580 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas20613 Professional/industrial Association Standard

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20613-4C15">https://military-fasteners.com/rivets/solid+rivets/MS20613-4C15</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.