

Description

Fastener Length: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206134C24
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-547-4190
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20613-4C24 Specifications

Fastener Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Shear Strength:	65000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66,300 Series Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	14 Type And C Grade

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-4C24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.