

Description

length: 7/16", diameter: 1/8", universal head corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206134C7
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-994-7081
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS20613-4C7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Shear Strength:	65000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Steel Comp 302 Overall
Material Document And Classification:	Qq-w-423,cond A Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-4C7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.