

Description

length: 1/4", diameter: 1/8", universal head, cadmium plated steel, roughly 620 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206134P4
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-994-7076
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20613-4P4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Shear Strength:	25000 Single Pounds Per Square Inch
Material:	Steel Comp 1005 Overall Or Steel Comp 1006 Overall Or Steel Comp 1008 Overall Or Steel Comp 1009 Overall Or Steel Comp 1010 Overall Or Steel Comp 1011 Overall Or Steel Comp 1012 Overall Or Steel Comp 1013 Overall Or Steel Comp 1015 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-4P4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.