

Description


Fastener Length: 3/4", roughly 190 pieces per pound, MS20613 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206135C12
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-068-2278
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS20613-5C12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Grip Length:	0.506 Inches Minimum And 0.526 Inches Maximum
Shear Strength:	65000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Steel Comp 302 Overall
Material Document And Classification:	Qq-w-423,cond A Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-5C12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.