



★ FASTENERS

Military-Fasteners.com

P/N MS20613-5C6

## Description

length: 3/8", diameter: 5/32", universal head, corrosion resistant steel, roughly 290 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS206135C6
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-995-1879
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20613-5C6 Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.160 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Grip Length:</b>	0.131 Inches Minimum And 0.151 Inches Maximum
<b>Shear Strength:</b>	65000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Comp 302 Overall
<b>Material Document And Classification:</b>	Qq-w-423,cond A Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-5C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.