

**Description**

Fastener Length: 1

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206136C16
Minimum Qty (MOQ):	50
NSN:	5320-00-777-5804
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20613-6C16 Specifications

<b>Fastener Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Shear Strength:</b>	65000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	66,300 Series Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	14 Type And C Grade

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-6C16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.