

Description

length: 1/4", diameter: 3/16", universal head - corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206136C4
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-777-5803
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N MS20613-6C4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	65000 Single Pounds Per Square Inch
Heat Treatment:	Annealed Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66,300 Series Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	14 Type And C Grade

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-6C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.