

Description

length: 1/4", diameter: 3/16", universal head - corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS206136C4 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-777-5803 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS20613-6C4 Specifications

| | |
|---|--|
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Shear Strength: | 65000 Single Pounds Per Square Inch |
| Heat Treatment: | Annealed Overall |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | 66,300 Series Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Nondefinitive Spec/std Data: | 14 Type And C Grade |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-6C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.