

**Description**

Fastener Length: 1/2, roughly 96 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206138C8
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-264-3183
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N MS20613-8C8 Specifications

<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.254 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.475 Inches Minimum And 0.525 Inches Maximum
<b>Shear Strength:</b>	65000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Annealed Overall
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	66,300 Series Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20613-8C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.