

Description

Fastener Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|--|
| SKU / Model: | MS206152M3 |
| Minimum Qty (MOQ): | 75 EA |
| NSN: | 5320-00-889-2678 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20615-2M3 Specifications

| | |
|--|--|
| Fastener Length: | 0.177 Inches Minimum And 0.197 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.027 Inches Minimum And 0.037 Inches Maximum |
| Shank Diameter: | 0.061 Inches Minimum And 0.065 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.119 Inches Minimum And 0.131 Inches Maximum |
| Grip Length: | 0.083 Inches Minimum And 0.103 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-2M3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.