

Description

length: 1/4", diameter: 3/32", universal head, monel, MS20615 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS206153M4 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-639-2697 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS20615-3M4 Specifications

| | |
|--|--|
| Fastener Length: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Grip Length: | 0.099 Inches Minimum And 0.119 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-3M4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.