

Description

length: 3/8", diameter: 3/32", universal head, monel, roughly 860 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206153M6
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-256-1935
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N MS20615-3M6 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Grip Length:	0.224 Inches Minimum And 0.244 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-3M6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.