

P/N MS20615-3M9

Description

Length: 9/16", diameter: 3/32", universal head, monel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information


SKU / Model: MS206153M9

Minimum Qty (MOQ): 50

NSN: 5320-00-808-0811

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc







^{*} See page 2 for technical characteristics

P/N MS20615-3M9 Specifications

| Fastener Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
|---------------------------------------|--|
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Grip Length: | 0.411 Inches Minimum And 0.431 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9 and selecting the quantity you want then