

## P/N MS20615-3M9

### **Description**

Length: 9/16", diameter: 3/32", universal head, monel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**


SKU / Model: MS206153M9

Minimum Qty (MOQ): 50

NSN: 5320-00-808-0811

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20615-3M9 Specifications

Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Grip Length:	0.411 Inches Minimum And 0.431 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9">https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9">https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9">https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9">https://military-fasteners.com/rivets/solid+rivets/MS20615-3M9</a> and selecting the quantity you want then