

Description

Fastener Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206154CU7
Minimum Qty (MOQ):	80 EA
NSN:	5320-00-777-5810
Schedule B:	7415.29.0000
ECCN:	EAR99
National Motor Freight:	096300, Rivets Brass / Bronze / Copper



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20615-4CU7 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Shear Strength:	17000 Single Pounds Per Square Inch
Material:	Copper Alloy Overall
Material Document And Classification:	Qq-w-341 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-4CU7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.