

P/N MS20615-4M12

Description

length: 3/4", diameter: 1/8", universal head, monel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS20615M4-12

SKU / Model: MS206154M12

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-256-1942

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N MS20615-4M12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20615-4M12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.