

Description

length: 3/4", diameter: 1/8", universal head, monel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS20615M4-12](#)

| | |
|-------------------------|--|
| SKU / Model: | MS206154M12 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-256-1942 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



* See page 2 for technical characteristics

P/N MS20615-4M12 Specifications

| | |
|--|--|
| Fastener Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Grip Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-4M12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.