

Description

Fastener Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206154M13
Minimum Qty (MOQ):	50 EA
NSN:	5320-00-787-7098
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20615-4M13 Specifications

Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.614 Inches Minimum And 0.634 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-4M13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.