

## P/N MS20615-4M15

### **Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS206154M15

Minimum Qty (MOQ): 40 EA

NSN: 5320-00-903-5077

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20615-4M15 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-4M15">https://military-fasteners.com/rivets/solid+rivets/MS20615-4M15</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.