

## P/N MS20615-4M16

### **Description**

length: 1", diameter: 1/8", universal head - monel"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS206154M16

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-833-2433

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20615-4M16 Specifications

| Fastener Length:                      | 0.990 Inches Minimum And 1.010 Inches Maximum      |
|---------------------------------------|--|
| Head Style:                           | Universal  |
| Head Height:                          | 0.054 Inches Minimum And 0.064 Inches Maximum      |
| Shank Diameter:                       | 0.124 Inches Minimum And 0.128 Inches Maximum      |
| Shank Style:                          | Straight   |
| Head Major Diameter:                  | 0.238 Inches Minimum And 0.262 Inches Maximum      |
| Grip Length:                          | 0.802 Inches Minimum And 0.822 Inches Maximum      |
| Shear Strength:                       | 49000 Single Pounds Per Square Inch                |
| Material:                             | Nickel Alloy 400 Overall                           |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-4M16">https://military-fasteners.com/rivets/solid+rivets/MS20615-4M16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.