

P/N MS20615-4M6

Description

length: 3/8", diameter: 1/8", universal head, monel, roughly 435 pieces per pound, MS20615 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS206154M6

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-844-1851

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc







^{*} See page 2 for technical characteristics

P/N MS20615-4M6 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20615-4M6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.