

Description

Fastener Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS206154MP13 |
| Minimum Qty (MOQ): | 145 EA |
| NSN: | 5320-00-171-6182 |
| Schedule B: | 7508.90.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20615-4MP13 Specifications

| | |
|---|---|
| Fastener Length: | 0.802 Inches Minimum And 0.822 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-4MP13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.