

Description

length: 3/16", diameter: 5/32", universal head, monel, roughly 375 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20615M3
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-482-0338
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS20615-5M3 Specifications

Fastener Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Minimum Tensile Strength:	49000 Pounds Per Square Inch
Material:	Copper Alloy Overall
Material Document And Classification:	Qq-n-281, CI A Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, CI 2 Fed Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-5M3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.