



Military-Fasteners.com

P/N MS20615-5M3

Description

length: 3/16", diameter: 5/32", universal head, monel, roughly 375 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206155M3
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-482-0338
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20615-5M3 Specifications

<b>Fastener Length:</b>	0.177 Inches Minimum And 0.197 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Minimum Tensile Strength:</b>	49000 Pounds Per Square Inch
<b>Material:</b>	Copper Alloy Overall
<b>Material Document And Classification:</b>	Qq-n-281, CI A Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty 2, CI 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-5M3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.