

# P/N MS20615-5M5

### **Description**

length: 5/16", diameter: 5/32", universal head, monel, roughly 290 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### MS20615-5M5W

SKU / Model: MS206155M5

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-685-0821

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20615-5M5 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Grip Length:	0.068 Inches Minimum And 0.088 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-5M5">https://military-fasteners.com/rivets/solid+rivets/MS20615-5M5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.